PENTAX | PLP-110 Series

RELIABLE WIDE RANGE LASER LEVEL PLP-115 | PLP-115G

- Wider Space: Range 600m (Radius 300m)
- 2 Kinds of Laser Color: Red(PLP-115) / Green(PLP-115G)
- Set and Start: Built-in self-leveling system
- Any Environments: Protection against water and dust (IP56)
- Multifunction: Scanning mode and manually slope the laser line(8%)
- Any Direction:





Technical Specifications PLP-115 / PLP-115G


Model Working Area			PLP-115	PLP-115G	
			600m (Radius 300m)		
Accuracy	Rotating laser	Horizontal setting	±15"		
		Vertical setting	±20"		
	Upper beam	Horizontal setting	±20"		
		Vertical setting	±30"	a .	
	Lower beam	Horizontal setting	±60"		
		Vertical setting	±60°		
Laser Class (Bottom laser is red)			Class 3R		
Visible Diode			635nm (Red)	515nm (Green)	
Laser Output			≤3mW		
Bottom Laser Output			≤ 0.6mW		
Rotation Speed			150, 300, 600 rpm		
Beam Scanning			Available		
Slope Setting			Slope 8% (Manually operated)		
Self-leveling Method			2 axes with DC motor system		
Self-levelin	ig Range		5°±1°		
Battery			C Batteries x 4		
Battery Life			20 hours (Alkaline)	12 hours (Alkaline)	
Operating Temperature			-10°C ~ 50°C		
Size			180 x 122 x 170		
Weight			1.5kg ± 5%		
Water / Dust Protection			IP56		
Accessories			Carrying Case		
			Detector (With Rod adapter)		
			Manual		
			Remote controller		

^{*} Appearance and specifications are subject to change without notice


Detector

Display	2 display / Front and Rear			
Wide	±2.5mm			
Narrow	±1mm			
Sound Level	3			
Battery	1x 9V Battery (supplied)			
Operating Temperature	-10°C ~ 50°C			


Horizontal & Vertical Laser Rotation and Scanning



Horizontal setting



Manual slope setting using Remote Controller





vertical setting



Automatic compensation

2 Kinds of Laser Color





TI Asahi Co., Ltd. International Sales Department

4-3-4 Ueno lwatsuki-Ku, Saitama-Shi Saitama, 339-0073 Japan

Exclusive PENTAX Distributor in IRAN

www.jahedteb.ir



197 Mirza Shirazi St. Motahari Ave.

Tehran - IRAN

Postal Code: 1586693111

Tel: +98 21 88315000 (20 lines)

Fax: +98 21 88314999







Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.