


**PENTAX** | R-1500N Series

# Total Surveying Solution

- Long EDM range measuring distance in reflectorless up to 500m and in prism mode up to 3,000m
- Large internal memory: 60000 points.
- Dual display as a standard equipment
- Easy transfer to a PC via SD card, USB mini and RS-232C data port
- Pre-loaded versatile software functions
- Dual battery system for long time use



**INCREASE YOUR  
WORK EFFICIENCY**

**FASTER  
TURNAROUND**



Model	R-1501N	R-1502N	R-1503N	R-1505N
<b>Telescope</b>	Image		Erect	
	Magnification		30 x	
	Effective Aperture		45mm	
	Resolving Power		3.0"	
	Field of View		1°20'	
	Minimum Focus		1.0m	
	Focus		Manual	
	Laser Class		Visible Laser: Class IIIa (Reflectorless, sheet) / Class I (Prism)	
	<b>Measurement Range (Good condition) *3</b>			
	Reflectorless *1		1.5 ~ 500m	
	Reflector Sheet *2		1.5 ~ 800m	
	Mini Prism		1.5 ~ 800m	
	1P		1.5 ~ 3000m	
	3P		1.5 ~ 5000m	
<b>Accuracy</b>	Prism		±(2+2ppm x D)mm	
	Reflector Sheet		±(3+2ppm x D)mm	
	Reflectorless		2.0m ~ 200m: ±(3+2ppm x D)mm	
			200m ~ 300m: ±(5+2ppm x D)mm	
			300m ~ 500m: ±(10+2ppm x D)mm	
Minimum Count		0.1mm (Fine mode), 1mm (Normal mode), 10mm (Track mode)		
<b>Measurement Time *4</b>	Repeat Meas.	Fine (0.1mm)	Prism / Refsheet 3.0sec., Refless 3.0sec. (over 300m 5.0sec.)	
		Normal (1mm)	Prism / Refsheet 2.0sec., Refless 2.0sec. (over 300m 4.0sec.)	
		Track (10mm)	Prism / Refsheet 0.4sec., Refless 0.4sec. (over 300m 0.4sec.)	
	Initial Meas.	Fine (0.1mm)	1.5 ~ 300m 3.5sec., over 300m ~ 13sec.	
		Normal (1mm)	1.5 ~ 300m 2.4sec., over 300m ~ 12sec.	
		Track (10mm)	1.5 ~ 300m 2.5sec., over 300m ~ 12sec.	
<b>Angle Measurement</b>	Measuring Method		Absolute rotary encoder	
	Detection Method		Vertical / Horizontal angle	
	Minimum Count		2 sides	
	Accuracy (ISO17123-3)	1"	2"	3"
<b>Compensator</b>			2 axis	
<b>Compensator range</b>			3' 30"	
<b>Tangent Screw</b>			1 Speed/Clamping (<30°)	
<b>Sensitivity of Vials</b>	Plate Level		30"/1 div. (electrical)	
	Circular Level		8'/2mm	
<b>Plummet</b>			Visible Laser, ±0.5mm (instrument height 1.5m)	
<b>Base</b>			Detachable	
<b>Dust and Water Protection</b>			IP55 (instrument only)	
<b>Ambient Temperature</b>			-20°C ~ 50°C / -4°F ~ 122°F (Working range)	
<b>Tripod Thread</b>			5/8"x 11	
<b>Dimensions/Weight</b>	Dimensions		183 (W) x 342(H) x 167(L)mm	
	Weight (incl. Battery)		5.4 kg	
<b>Carrying Case</b>			440(W) x 370 (H) x 275 (L)mm /3.9 kg	
<b>Battery Pack</b>	Power Source		Li-ion 2,500mAh X 2 = 5,000mAh (hotswap)	
	Operation Time		Continuous approx. 9.0 hrs (ETH+EDM) with approx. 2.5hrs. of charging time	
	Weight		5400g	
<b>Battery Charger and AC Adapter</b>				
	Input Voltage (AC05)		AC 100 ~ 240V	
	Output Voltage (BC05)		DC8.4V	
<b>Data Process</b>	Data Recording Method		Internal Memory	
	Capacity / Coordinates Data		Up to 2GB / 60000	
	Special Function		PowerTopoExpress 2	
	I/F		RS-232C, SD CARD, USB mini, Bluetooth (class2)	
<b>Display / Keyboard</b>	Display Type		Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels	
	Quantity		2	
	Keys		22 each (12 numeric / 5 function / 5 special)	
<b>Display Back Light</b>			Intensity settings: 10 steps	
<b>Laser Pointer</b>			Yes	
<b>Date Clock</b>			Yes	

\* Specifications are subject to change without notice

- \*1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment.  
The measurement range of reflectorless is determined by the white side of the Kodak Gray Card.
- \*2 Reflector sheet: Genuine Reflector sheet
- \*3 The measurement range may vary by conditions of the environment.  
Normal conditions: 20km visibility with slight shimmer  
Good conditions: 40km visibility with overcast, no heat, no shimmer and moderate wind.
- \*4 EDM measuring time is determined in good conditions. It may takes longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode.

**TI Asahi Co., Ltd.**  
International Sales Department  
4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi  
Saitama, 339-0073 Japan

Exclusive PENTAX Distributor in IRAN

[www.jahedteb.ir](http://www.jahedteb.ir)



197 Mirza Shirazi St. Motahari Ave.  
Tehran - IRAN  
Postal Code : 1586693111  
Tel : +98 21 88315000 (20 lines)  
Fax : +98 21 88314999



The CE marking assures that this product complies with the requirements of the EC directive for safety.

**JSIMA**  
Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

